




SEALING SYSTEMS



AdvantaTube™ Sterile Welder



The AdvantaTube™ Welder makes sterile tubing welds quickly, reliably, and easily. Developed for biopharmaceutical applications, the AdvantaTube Welder has been designed to optimally work in all AdvantaFlex® tubing applications including wet, dry, or fluid filled tubing.

Sterile connections are made in as few as three minutes. Automated functions assure proper temperature and tubing placement, and the unit welds both gamma irradiated and autoclaved TPE tubing.



KEY FEATURES

- Designed specifically for biopharmaceutical process applications
- Maintains sterility of wet, dry, or fluid filled tubing welds
- Easy to use — self controlled heating operation and automated mechanical motion
- Rugged table top unit weighs only 25 lbs.
- An LCD display prompts the operator
- Preprogrammed for AdvantaFlex TPE (thermoplastic elastomer) tubing; program settings for other TPE tubing are available
- Single use blades assure sterility; built in sensor prevents blade reuse
- Tubing grippers position, align, and secure tubing in place
- Interior clamps close fluid filled tubing; no need for other clamping devices
- A replaceable HEPA filter and positive air pressure help control particulate
- Cycle time averages 3 minutes
- Welds both gamma irradiated and autoclaved AdvantaFlex tubing
- Replacement blades and HEPA filters stocked
- Certificate of Compliance provided with each AdvantaTube Welder
- Standard 110 VAC power input; 230 VAC and various plug adaptors available
- One year warranty



TPE WELDER
www.advantapure.com

SPECIFICATIONS

■ Model 3960 Sterile AdvantaFlex® Tubing Welder

Size & Weight	
Dimensions	12 x 13 x 9.5 inches 30.5 x 33 x 24.1 cm
Operating Weight	25 lbs 11.35 kg
Electrical	
Certifications	cTUVus, CE, WEEE
Power Input	110 VAC, 50-60 Hz, 2.4 amps 230 VAC, 50-60 Hz, 3.1 amps
Main Fuses	110 VAC units: 1.6A-T 250 VAC 230 VAC units: 0.8A-T 250 VAC
Tubing Sizes	0.375" - 0.750" O.D., 0.0625" - 0.125" wall thickness
Operating Conditions	
Temperature	68° - 110°F 20° - 43°C
Humidity	90% maximum relative humidity, non-condensing
Compressed Air Requirements	minimum 60 psi, 85-100 optimal 1/4" male stem quick connect fitting

Purity in Fluid Flow Systems®



Made in U.S.A.

AdvantaPURE®
NEWAGE INDUSTRIES



DISTRIBUTED BY:

SEALING SYSTEMS

Engineering Equipment for Sanitary Applications
90, Kifisias Ave. Maroussi GREECE Tel +30 210 8764820
www.sealingsystems.gr

©2012 NewAge® Industries, Inc. Specifications are subject to change without notice.
AdvantaPure products are produced by NewAge® Industries, Inc.
AdvantaFlex®, AdvantaTube™, Purity in Fluid Flow Systems®, NewAge Industries AdvantaPure®, NewAge®, and the "N" logo are trademarks of NewAge® Industries, Inc.

NEWAGE INDUSTRIES **ESOP** Employee Owned
for Your Benefit

NOTE: It is the user's responsibility to ensure the suitability and safety of NewAge Industries AdvantaPure products for all intended uses. The user is responsible for any required testing. Any data supplied by NewAge Industries AdvantaPure is provided as a helpful guideline and is believed to be reliable; however, nothing stated shall constitute a guarantee, recommendation, or warranty for any application. All advice is given and accepted at the buyer's risk.
WARRANTY: NewAge Industries AdvantaPure products are warranted to be free from defects in material and workmanship. Any product found to carry such defects will be replaced without charge. This warranty is limited only to the replacement of NewAge Industries AdvantaPure products, item for item, which after examination by NewAge Industries AdvantaPure are deemed defective. The user assumes all other risk, including that of injury, loss or damage, direct or indirect, resulting from the use, misuse, or inability to use this product. NewAge Industries AdvantaPure specifically disclaims any other liability or warranty, express, implied or statutory and including without limitation, any and all warranties of merchantability or fitness for a particular purpose.
NOTICE: NewAge Industries, Inc. has been a privately owned corporation since 1954. Neither the corporation nor its principals are affiliated, in any way, with any other group or entity either representing themselves as or being referred to by the term NewAge.